

LAKE LED light Series/ Foco LED Gama LAKE

Our LAKE light with submersible LED technology, crafted from IP68 stainless steel and designed expressly for fountain lighting, ponds and gardens, houses a high-performance AR-111 LED bulb. It is manufactured from 1 mm sheeting using a stainless steel stamping process, making it both extremely light and resistant to corrosion and aging processes.

Nuestro foco LAKE con tecnología LED sumergible de acero inoxidable IP68, está expresamente diseñado para iluminación de fuentes ornamentales, estanques y jardines, alberga en su interior una lámpara LED de alto rendimiento tipo AR-111. Está fabricado mediante el proceso de estampación de acero inoxidable con chapa de 1 mm lo cual hace que sea muy ligero y resistente a procesos de corrosión.



Certifications/ Certificaciones IP68 CE



Lighting/
Iluminación

PRODUCT FEATURES/ CARACTERÍSTICAS DEL PRODUCTO

- Fabricado en acero Inoxidable AISI 304
- IP 68 Certificado por laboratorio externo
- Iluminación RGB, blanca 6000K y blanca 3000K
- Versatilidad de instalación al disponer de modelos con 2PG entradas/salidas posibilitando la conexión en paralelo. Tapón final también suministrado.
- Conector IP 68 con protección adicional X-dry que asegura una barrera para la entrada de condensación.
- LEDs de última generación y elevado rendimiento lumínico.
- Disponibles con lentes de 10° o 30°
- LED's auto protegidos de polaridad inversa
- Tensiones de entrada de 12 y 24Vdc
- Gran superficie de evacuación de calor, dando durabilidad a los leds
- Made of stainless steel AISI 304
- IP 68 Certified by an external laboratory
- RGB lighting, white 6000K and white 3000K
- Installation versatility by having models with 2PG inlet/ outlet allowing parallel connection. End cap also supplied.
- IP68 Connector with additional X-dry protection that ensures a barrier to the entry of condensation.
- Latest generation LEDs and high performance lighting.
- Available with 10° or 30° lenses.
- Reverse polarity self-protected LEDs.
- 12 and 24Vdc input voltages
- Large heat evacuation surface, giving durability to the LEDs

LAKE LED light Series/ Foco LED Gama LAKE

Electrical data/ Datos eléctricos


Reference/ Referencia	Model/ Modelo	Colour/ Color	Beam angle/ Ángulo	Lumens/ Lúmenes	Power/ Potencia	Voltage/ Voltaje	Lamp/ Lámpara	Electrical connection/ Conexión eléctrica	Outlet N°. and type/ N°. de salidas y tipo	Weight/ Peso	Material/ Material
F5200031	250	White/ 6500K	10°	772 Lm	11W	12/24V DC	F5643044	G 53 Lamp	* 2 x PG 16 Type of cable**/ Tipo de cable** Ø6/9/12	1,7 kg	Stainless steel AISI-304/ Acero Inoxidable AISI-304
F5200029			30°				F5643011				
F5205058		RGB	10°	635 Lm	13,2W		F5643551	R, G, B, COM Lamp			
F5205047			30°				F5643527				
F5185135			10°	593 Lm	27W		-	R, G, B, COM Connector/ Conector	1 x Plug & Socket/ Conector enchufable IP68 Connector Type of cable**/ Tipo de cable ** Ø7-Ø12		
F5185113			30°				-				
F5207038	500	White/ 3000K	10°	1150 Lm	13,2W		F5643088	G 53 Lamp	* 2 x PG 16 Type of cable**/ Tipo de cable** Ø6/9/12		
F5207027			30°				F5643066				
F5200007	Without lamp/ Sin lámpara							-		1,4 kg	

*Optional/ Opcional 2 x PG-21 Ø11,7/Ø15/Ø18,6 Add "P" letter at the end of the reference/ Añadir una "P" al final de la referencia

Dimensions/ Dimensiones


250 PG

500 PG




250

Plug & Socket/ Conector enchufable IP68



Protection Grid/ Rejilla F5662405



Light charts/ Datos de iluminación

10°

Distance/ Distancia	Beam/ Haz de luz (m)	250			500
		White 6000K	RGB 635 Lm	RGB 593 Lm	White 3000K
1 m		8100 lx	9220 lx	10236 lx	8800 lx
2 m		2025 lx	2305 lx	2559 lx	2220 lx
3 m		900 lx	1024 lx	1137 lx	978 lx
4 m		506 lx	576 lx	640 lx	550 lx
5 m		324 lx	369 lx	409 lx	352 lx

30°

Distance/ Distancia	Beam/ Haz de luz (m)	250			500
		White 6000K	RGB 635 Lm	RGB 593 Lm	White 3000K
1 m		6376 lx	6592 lx	4866 lx	7540 lx
2 m		1594 lx	1648 lx	1216 lx	1885 lx
3 m		708 lx	732 lx	540 lx	838 lx
4 m		398 lx	412 lx	304 lx	471 lx
5 m		255 lx	264 lx	194 lx	302 lx

250 PG

500 PG



250 Plug & Socket/ Conector enchufable IP68

